


NORTHAMPTON COUNTY



Mark Cline
Building Official

Building Department
P.O. 538
Eastville, VA 23347
Phone: (757) 678-0445
Fax: (757) 678-0483

Asbestos Regulations Compliance Form

1996 Virginia Uniform Statewide Building Code
Section 108.10 / Code of Va. §36-99.7

Job location _____

1. Is this permit for work on a building or portions thereof constructed after January 1, 1985?
No - Please go to question 2. **Yes - Please sign the back this form**
2. Is this permit for work on a single family dwelling or an apartment building with 4 or less units?
No - Please go to question 4. **Yes - Please go to question 3.**
3. Does this permit involve the demolition of a residential building for commercial development?
No - **STOP - Please sign the back of this form.** Yes - Please go to line 6.
4. Does this *nonresidential* permit involve *only* re-roofing, re-flooring or re-siding?
No - Please go to question 5. Yes - Please go to line 9.
5. Does this permit involve disturbing, altering or removing:
 - more than 260 linear feet of existing piping?
 - more than 160 square feet of other existing building components?
 - more than 35 cubic feet of facility components that cannot be measured?**No - STOP- Please sign the back of this form.** Yes - Please go to line 6.
6. Has this building been inspected by a Virginia Certified Asbestos Inspector?
No - **Please go to line 7.** Yes - **Please go to line 8.**
7. This building is required to be inspected by a Virginia Certified Asbestos Inspector. Please have this building inspected for asbestos and re-file this form.
8. If asbestos has been found in areas affected by construction, it is the owners responsibility to comply with all Federal and State asbestos laws, including permits from the Virginia Department of Labor and Industry, OSHA and DOT. **Sign the back of this form, and pick up a re-certification form.**

FORM CONTINUED ON THE OTHER SIDE OF THIS PAGE

9. The asbestos regulations require:

- that this work be inspected by a Virginia Certified Roofing/Flooring/Siding (RFS) Asbestos inspector. If asbestos is found, work must be done by a Virginia licensed RFS contractor or a Virginia licensed asbestos abatement contractor.

OR

- that this work be assumed to contain asbestos, and work will be performed by a Virginia licensed RFS contractor or a Virginia licensed asbestos abatement contractor.

I understand that this form is a legal document and that, by signing it, I am making a legally binding claim. I am the property owner. legal agent for the property owner.

Signature _____ Date _____

§ 36-99.7. Asbestos inspection in buildings to be renovated or demolished; exceptions. A. A local building department shall not issue a building permit allowing a building to be renovated or demolished until the local building department receives certification from the owner or his agent that the affected portions of the building have been inspected for the presence of asbestos by an individual licensed to perform such inspections pursuant to § 54.1-503 and that no asbestos-containing materials were found or that appropriate response actions will be undertaken in accordance with the requirements of the Clean Air Act National Emission Standard for the Hazardous Air Pollutant (NESHAPS) (40 CFR 61, Subpart M), and the asbestos worker protection requirements established by the U.S. Occupational Safety and Health Administration for construction workers (29 CFR 1926.58). Local educational agencies that are subject to the requirements established by the Environmental Protection Agency under the Asbestos Hazard Emergency Response Act (AHERA) shall also certify compliance with 40 CFR 763 and subsequent amendments thereto.

B. To meet the inspection requirements of subsection A except with respect to schools, asbestos inspection of renovation projects consisting only of repair or replacement of roofing, floorcovering, or siding materials may be satisfied by:

1. A statement that the materials to be repaired or replaced are assumed to contain asbestos and that asbestos installation, removal, or encapsulation will be accomplished by a licensed asbestos contractor or a licensed RFS contractor; or
2. A certification by the owner that sampling of the material to be renovated was accomplished by an RFS inspector as defined in § 54.1-500 and analysis of the sample showed no asbestos to be present.

C. The provisions of this section shall not apply to single-family dwellings or residential housing with four or fewer units, unless the renovation or demolition of such buildings is for commercial or public development purposes. The provisions of this section shall not apply if the combined amount of regulated asbestos-containing material involved in the renovation or demolition is less than 260 linear feet on pipes or less than 160 square feet on other facility components or less than thirty -five cubic feet off facility components where the length or area could not be measured previously.

D. An abatement area shall not be reoccupied until the building official receives certification from the owner that the response actions have been completed and final clearances have been measured. The final clearance levels for reoccupancy of the abatement area shall be 0.01 or fewer asbestos fibers per cubic centimeter if determined by Phase Contrast Microscopy analysis (PCM) or 70 or fewer structures per square millimeter if determined by Transmission Electron Microscopy analysis (TEM).